

Centrifugal Basket Mill ACBM

www.jegerings.com



JEGERINGS.COM B.V.

Stationsstraat 130 5751 HJ Deurne The Netherlands T +31(0)493-31 23 71

M +31 (0)6-47 88 09 84

E info@jegerings.comI www.jegerings.com

IBAN
BIC (SWIFT)
BTW/VAT no.
KvK/Trade reg.

NL14 ABNA 0454 7116 70 ABNANL2A NL 8628 32 251 B01 83330925



General

The basket mill ACBM helps to reduce the waste of falling vegetables significantly. The ACBM is designed to place behind a vegetable washing machine. The ACBM's optical sensor detects when the basket is full and subsequently the carousel automatically rotates to the next position with an empty basket. This rotation happens very fast and vegetables that did not make it into the basket are caught by the feed hopper and put into the next basket. The machine is made completely of stainless steel for perfect hygiene and longevity. The ACBM basket can be seamlessly integrated in a vegetable processing line for cutting, washing and drying vegetables.



The ACBM in a vegetable processing line for cutting, washing and drying vegetables

Video processing line for small to medium capacity

Options



Centrifugal basket 44 l

This centrifugal basket (or also called spinner basket) is the standard size basket that can be used for the ACBM basket mill as well as every model dryer in our product line. The baskets have been tested by Intertec Polychemlab and can be used for handling all kind of food stuff and vegetables.



Mesh basket insert

This mesh insert basket is especially designed for vegetables and other products that are cut into very small dimensions as it has a much smaller perforation (1x1mm) than the centrifugal baskets. The insert is supposed to be placed within the centrifugal basket and will make sure that small cut product will not got lost through the perforation of the basket.



Centrifugal basket trolley

With this trolley full (and heavy) centrifugal baskets can easily be moved around the processing facility. This trolley is made of stainless steel.



Technical data

Capacity	4 baskets per minute
Electrical data	1 Ph / 230 V / 1.1 A*
Power	0.55 kW
Dimensions	1550 x 1400 x 1700 mm
Weight	190 kg

^{*}The ACBM is electrically adaptable ensuring its compatibility with local power requirements.

Dimensional drawing



